

Distributed by:

JAMECO[®]
ELECTRONICS

www.Jameco.com ♦ 1-800-831-4242

The content and copyrights of the attached
material are the property of its owner.

Jameco Part Number 1468051

Surface Mount Type


SP-Cap

Series: S

- Features
 - Super Low-ESR(5 to 9mΩ)
 - Lower ESR and Higher Capacitance at the same case size as conventional products.
 - Excellent Noise-absorbent Characteristics
 - High Ripple Current
 - RoHS directive compliant
 - Reflow 260°C and 240°C. Please see specific P/N details.

Country of Origin


Japan
Singapore




■ Specification

Series & Size Code	SL	SX	SD	SE
Category Temp.Range	-40 to +105°C			
Rated W.V.Range	2 to 6.3V.DC			
Nominal Cap.Range	56 to 220μF	68 to 330μF	120 to 390μF	180 to 560μF
Capacitance Tolerance	±20 %			
DC Leakage Current	Reflow 240°C: I ≤ 0.06 CV 2minutes(2 to 4V.DC) I ≤ 0.04CV 2minutes(6.3V.DC) Reflow 260°C: I ≤ 0.1CV 2minutes			
tan δ	≤ 0.06(120Hz/ +20°C)		≤ 0.10(120Hz/ +20°C)	
Surge Voltage	Rated Working Voltage × 1.25 (15 to 35°C)			
Endurance	After applying rated working voltage for 1000 hours at 105±2°C, and then being stabilized at +20°C, capacitor shall meet the following limits.			
	Capacitance change	±10% of initial measured value		
	tan δ	≤ Initial specified value		
	DC leakage current	≤ Initial specified value		
Moisture resistance	After storing for 500 hours at 60°C,90%			
	Capacitance change of initial measurd value	2, 2.5V.DC +70, -20%	4 V.DC +60, -20%	6.3V.DC +50, -20%
	tan δ	≤ 200% of initial specified value		
	DC leakage current	≤ Initial specified value		

■ Marking



■ Dimensions in mm(not to scale)



(mm)

Series & Size Code	L±0.2	W1±0.2	W2±0.1	H	P±0.3
SL	7.3	4.3	2.4	1.8±0.1	1.3
SX	7.3	4.3	2.4	1.9±0.2	1.3
SD	7.3	4.3	2.4	2.8±0.2	1.3
SE	7.3	4.3	2.4	4.2±0.1	1.3

■ Low ESR Products


Series & Size Code	Rated W.V. (V.DC)	Capaci- tance (±20%) (μF)	Case Size			Specification		Reflow 240°C	Reflow 260°C	Min. Packaging Q'ty (pcs)
			L (mm)	W (mm)	H (mm)	*1 Ripple current (Ar.m.s.)	*2 ESR (Ω)	Part number	Part number	
SL	2	100	7.3	4.3	1.8	3.0	0.009	EEFSL0D101R	EEFSL0D101ER	3500
		120	7.3	4.3	1.8	3.0	0.009	EEFSL0D121R	EEFSL0D121ER	3500
		150	7.3	4.3	1.8	3.0	0.009	EEFSL0D151R	EEFSL0D151ER	3500
		180	7.3	4.3	1.8	3.0	0.009	EEFSL0D181R	EEFSL0D181ER	3500
		220	7.3	4.3	1.8	3.0	0.009	EEFSL0D221R	EEFSL0D221ER	3500
	2.5	100	7.3	4.3	1.8	3.0	0.009	EEFSL0E101R	EEFSL0E101ER	3500
		120	7.3	4.3	1.8	3.0	0.009	EEFSL0E121R	EEFSL0E121ER	3500
		150	7.3	4.3	1.8	3.0	0.009	EEFSL0E151R	EEFSL0E151ER	3500
	4	82	7.3	4.3	1.8	3.0	0.009	EEFSL0G820R	EEFSL0G820ER	3500
	6.3	56	7.3	4.3	1.8	3.0	0.009	EEFSL0J560R	—	3500
SX	2	180	7.3	4.3	1.9	3.0	0.009	EEFSX0D181R	EEFSX0D181ER	3500
		220	7.3	4.3	1.9	3.0	0.009	EEFSX0D221R	EEFSX0D221ER	3500
		270	7.3	4.3	1.9	3.0	0.009	EEFSX0D271R	EEFSX0D271ER	3500
		330	7.3	4.3	1.9	3.0	0.009	EEFSX0D331R	EEFSX0D331ER	3500
	2.5	150	7.3	4.3	1.9	3.0	0.009	EEFSX0E151R	EEFSX0E151ER	3500
		180	7.3	4.3	1.9	3.0	0.009	EEFSX0E181R	EEFSX0E181ER	3500
	4	82	7.3	4.3	1.9	3.0	0.009	EEFSX0G820R	EEFSX0G820ER	3500
		100	7.3	4.3	1.9	3.0	0.009	EEFSX0G101R	EEFSX0G101ER	3500
	6.3	68	7.3	4.3	1.9	3.0	0.009	EEFSX0J680R	—	3500
SD	2	270	7.3	4.3	2.8	3.5	0.007	EEFSD0D271R	EEFSD0D271ER	2000
		330	7.3	4.3	2.8	3.5	0.007	EEFSD0D331R	EEFSD0D331ER	2000
		390	7.3	4.3	2.8	3.5	0.007	EEFSD0D391R	EEFSD0D391ER	2000
	2.5	220	7.3	4.3	2.8	3.5	0.007	EEFSD0E221R	EEFSD0E221ER	2000
		270	7.3	4.3	2.8	3.5	0.007	EEFSD0E271R	EEFSD0E271ER	2000
	4	150	7.3	4.3	2.8	3.5	0.007	EEFSD0G151R	EEFSD0G151ER	2000
	6.3	120	7.3	4.3	2.8	3.5	0.007	EEFSD0J121R	—	2000
SE	2	390	7.3	4.3	4.2	4.0	0.005	EEFSE0D391R	EEFSE0D391ER	2000
		470	7.3	4.3	4.2	4.0	0.005	EEFSE0D471R	EEFSE0D471ER	2000
		560	7.3	4.3	4.2	4.0	0.005	EEFSE0D561R	EEFSE0D561ER	2000
	2.5	330	7.3	4.3	4.2	4.0	0.005	EEFSE0E331R	EEFSE0E331ER	2000
		390	7.3	4.3	4.2	4.0	0.005	EEFSE0E391R	EEFSE0E391ER	2000
	4	220	7.3	4.3	4.2	4.0	0.005	EEFSE0G221R	EEFSE0G221ER	2000
	6.3	180	7.3	4.3	4.2	4.0	0.005	EEFSE0J181R	—	2000

*1: Ripple current (100kHz/ +20 to +105°C),


*2: ESR (100kHz/+20°C)

■ Mounting Specifications.


● Recommendable reflow soldering temperature 240°C



● Recommendable reflow soldering temperature 260°C




● Typical land pattern (mm)




■ Packaging Specifications

● Reel Dimensions (mm)



● Embossed Taping (mm)



■ Packaging Box Dimensions (mm)

